



Used Liouy Hsing 530 x 1100 Lathe

Standard Accessories

3-Jaw Chuck 9"

Center Sleeve M.T. No.6 x 4

Dead Center M.T. No.4

Levelling Screws

Service Kits

Main Motor 5HP(4P)

Steady Rest

Drive Plate

Complete Coolant Equipment

Specifications for Used Liouy Hsing 530 x 1100 Lathe

Capacity	
Width Of Bed	300 (12") mm
Total Travel Of Top Slide	120 (4 3/4") mm
Swing Over Bed	Ø532 (21") mm
Swing Over Cross Slide	Ø372 (14 2/3")mm
Swing In Gap	Ø710 (28") mm
Gap Width in front of face plate	150 (5 7/8") mm
Height of Center from leg bottom	1080 (46") mm
Distance Between Centers	550 (21.65") / 800(32") / 1100 (44") /1700 (67") / 2000(78.74")
Headstock	
Number of Spindle Speeds	12 steps
Spindle Bore	Ø58 (2 1/4") mm
Type of Spindle Nose	ASA-A1-6 D1-6
Taper of Spindle Bore & Center	MT. NO. 6 x No. 4
Range of Spindle Speeds	35,52,75,110,160,230,330,490,650,950,1350,2000
Thread & Feed	
Lead Screw Diameter and Pitch	35(1 1/8") 4TPI or pitch 6mm
Range Of Inch Threads	2~72(44 changes)
Range Of Metric Threads	6mm: 0.2~14 (39)changes
Number Feeds	36 steps
Range Of Longitudinal Feeds	0.03~0.85mm(0.0012"~0.034")
Range Of Cross Feeds	1/2 of longitudinal feeds
Tailstock	
Tailstock Quill Diameter	Ø60(2 3/8")
Total Travel of Tailstock Quill	150(6")
Taper In Tailstock Quill	No. 4
Motors	
Spindle Drive Motor	5 HP/ 7.5HP(opt.)

Specifications for Used Liouy Hsing 530 x 1100 Lathe

Motors

Coolant Pump Motor	1/8
--------------------	-----

Machine Dimensions & Weight

Packing Dimensions (L x W x H)	2300 x 1060 x 1500mm				
Net weight (approximate)	1700 Kgs				